



Sway Bar Mounts for Polaris RZR XP1K & XP Turbo

SKU#360-90411

Introduction

- Designed to be more durable and lightweight than stock sway bar mounts.
- Sway bar mounts are made of billet aluminum 6061.
- Installation requires a qualified mechanic.
- Read instructions carefully and study the pictures before attempting installation.
- Check the parts and hardware packages against the parts list to assure that your kit is complete.
- Always wear safety glasses when using power tools.
- This instruction set available in color on www.cognitomotorsports.com

Requirements

- Requires 10 mm drill bit to drill out holes on frame to fit new size carriage bolts.
- Hex bolt in hardware pack is for XP Turbo models with intercooler water pump bracket.

Parts List

ITEM NO.	PartNo	DESCRIPTION	QTY.
1	6203	Billet Sway Bar Mount	2
2	2374	Sway Bar Nut Plate	2
3	-	M10 x 1.5 x 50 mm Lg. Carriage Bolt	4
4	-	M10 Lock Nut	4
5	-	Washer	5
6	-	M10 x 1.5 x 55 mm Lg. Hex Head Bolt	1

Installation

1. Make sure your vehicle is properly supported so that removal of the sway bar does not allow the trailing arms to fall and cause injury.
2. Remove the OEM sway bar mounts from the frame. Remove the OEM bushings. They will be reused. You can optionally remove the bolt holding the sway bar end links to the sway bar to make installation a bit easier, but not required.
3. The Cognito sway bar mounts utilize 10 mm bolts. Drill out the square holes on the frame where the sway bar mounts mount to 10 mm.

NOTE: On the XP Turbo the intercooler water pump bracket shares a hole with the passenger side sway bar mount. Drill through both the frame and the water pump bracket and sandwich the nut plate between these two. Use the 10 mm hex bolt on the bottom hole here. If you are using our old gusset plates the bolt will have to pass through at an angle so this hole will have to be drilled out a bit oversized. Use a prybar to stop the hex bolt from spinning to tighten the bolt if you have the old gusset kit.

4. Using the supplied hardware. Bolt the sway bar and the Cognito sway bar mount to the frame. Use the nut plate provided to carriage the new 10 mm bolts into. Reattach the sway bar end links to the sway bar if you detached them in step 1. Torque nuts to 30 ft-lbs (40 Nm).



Figure 1: The frame holes need to be drilled out to 10 MM for the new carriage bolts to pass through. Use the nut plate to carriage the bolts as pictured. The notch in the nut plates is meant to clear the Cognito gusset plates and would be towards the top of the car if you have the gusset kit.

Cognito Motorsports

Limited Lifetime Warranty

Cognito Motorsports warrants, to the original retail purchaser, that its suspension products are free from defects in workmanship and material for as long as the purchaser owns the vehicle on which the product was originally installed. Cognito Motorsports does not warrant the product for finish, alterations, modifications, and/or original installation contrary to specifications of Cognito Motorsports. Cognito Motorsports suspension products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities involving abnormal abuse other than the vehicle was originally designed to handle or endure. (A "RACE" is defined as any contest between two or more vehicles, and/or contest of one or more vehicle against the clock, whether or not such contest is for a prize.)

This warranty is for a one-time replacement of each Cognito Motorsports product and does not cover any part that Cognito Motorsports has previously replaced under this warranty. This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warrant are sales outside of the United States of America. Alterations to the finish of the parts including but not limited to painting, powder coating, plating, and/or welding will void all warranties. Cognito Motorsports obligation under this warranty is limited to the repair or replacement, at Cognito Motorsports option of the defective product. Any and all costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty.

This warranty excludes the following items: bushings, bumpstops, tie-rod ends, limiting straps, and heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days of purchase for defects in workmanship. Cognito Motorsports suspension components must be installed as a complete system. Any substitutions or exemptions of required components will immediately void the warranty. Some finish damage may happen to parts during shipping and is not covered under warranty. This warranty shall not apply to any product that had been subject to accident, negligence, alteration, abuse, or misuse. Cognito Motorsports does not warrant products not manufactured by Cognito Motorsports. Cognito Motorsports reserves the right to supersede, discontinue, or change the design, finish, part number and/or application of parts when deemed necessary by Cognito Motorsports without written notice, and in the sole and absolute discretion of Cognito Motorsports.

Warranty Claims

All warranty claims must be submitted through the original company of purchase. All claims must be shipped back to the original company of purchase with an approved RMA number listed as a reference on the shipping label and clearly printed on two opposing sides of the package(s); product in question must be inspected by Cognito Motorsports before replacement parts are shipped out.

Return Policy

Cognito Motorsports has a no refund return policy. Under special circumstances, returns might be accepted with prior written approval. All returned product will be shipped freight prepaid. Product returned is subject to a 25% restocking fee. No returns will be accepted after 30 days upon receipt of product.

Product Consumer Safety and Warning

The installation of this kit will modify the suspension of your vehicle and may cause it to handle significantly different than a factory equipped vehicle. Installing larger tires with modified suspension and increased ground clearance will significantly alter the handling characteristics of the vehicle, and may result in increased braking distances as well as changes in vehicle maneuverability and handling compared to the factory equipped vehicle. As with any vehicle, extreme caution and care must be used to prevent loss of control or roll-over during sharp turns or abrupt maneuvers. Always wear seat belts and drive safely, recognizing the reduced speeds and specialized driving techniques is required.

This suspension system will not strengthen nor reinforce the stock frame of the vehicle, nor will it increase rollover protection. It is necessary to periodically inspect all suspension and drive train components for tightness of fit or any damage. Installation of these parts will modify the height of the vehicle and will raise the center of gravity. Altered height modifications and off-road operation may increase your vehicle's susceptibility to roll over conditions and may cause serious injury or death. Many states regulate the height modification to each vehicle. Check the laws in your state for exact specifications. Height modifications may affect the reaction, ride, handling, and wear factor of your vehicle's components.

Failure to drive this vehicle safely may result in injury or death! Do not drive this vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications and combinations of modifications are not recommended, unsafe, and may not be permitted in your state. Consult your vehicle owner's manual, the instructions accompanying this product, and your state laws before undertaking these modifications. The owner of the modified vehicle and the qualified mechanic required to install this product are responsible for the legality and safety of the vehicle being modified.